

Ölheizgeräte	K25	K50	K80	K120	K150	K160H	K170H	K220	K250R HTL	K500
Nennwärmebelastung (kW)	27	54	83	120	150	161	168	155/234	220	500
Luftleistung (m ³ /h)	2.050	4.200	6.500	8.900	8.900	12.600	11.000	11.400/14.100	13.860	28.550
Innere Pressung (Pa)	50	100	100	150	150	150	250	620	620	200
Geräusch (dB(A)) in 5 m Entfernung	58	59	67	72	72	77	52	72	74	90
Brennstoffverbrauch Öl (l/h)	2,7	5,5	8,5	12,5	14,8	16,5	16,5	15,5/22,1	24,5	49
Stromanschluss	230V	230V	230V	230V	230V	230V	400V/16A	400V/16A	400V/16A	400V/16A
Höhe Breite Tiefe (cm)	85x65x115	107x77x150	127x87x160	140x94x185	140x94x185	155x105x205	140x97x225	170x128x225	140x80x240	260x244x606
Gewicht (kg)	85	140	190	225	280	330	340	480	505	4.200
Tankinhalt (l)	35	externer IBC	externer IBC	externer IBC	externer IBC	externer IBC	externer IBC	externer IBC	externer IBC	externer IBC
Abgasrohr (mm)	150	150	150	200	200	200	200	200	200	k.A.
Ausblas DN (mm)	200/305	420	520	550	560	550	550	2x550	550	300